

<b>THOMSON</b>			
<b>DELPHION</b>	<b>RESEARCH</b>	<b>PRODUCTS</b>	<b>INSIDE DELPHION</b>
<a href="#">Home</a>	<a href="#">My Account</a>	<a href="#">Products</a>	<a href="#">Help</a>
Search: Quick/Number Boolean Advanced Derwent			

## The Delphion Integrated View

Get Now: <input checked="" type="checkbox"/> PDF   <a href="#">More choices...</a>	Tools: Add to Work File: <input type="checkbox"/> Create new Work File <input checked="" type="checkbox"/> <input type="button" value="Go"/>
View: <a href="#">INPADOC</a>   Jump to: <input type="text" value="Top"/> <input checked="" type="checkbox"/>	Go to: <a href="#">Derwent</a> <input checked="" type="checkbox"/> Email this to a friend

🔍 Title: **JP11219116A2: IMAGE FORMING BODY**

🔍 Derwent Title: Image formation sheet as label for ribbon printer, ink jet printer, thermosetting ink jet printer - has an image receiver sheet containing base material and adhesion sheet containing separator which have specific adhesion strength [\[Derwent Record\]](#)

🔍 Country: **JP Japan**

🔍 Kind: **A** (See also: [JP3035650B2](#) )

🔍 Inventor: **KOTANI KOZO;**  
**KOSAKA MIYOJI;**

🔍 Assignee: **REIKO CO LTD**  
[News, Profiles, Stocks and More about this company](#)

🔍 Published / Filed: **1999-08-10 / 1998-01-30**

🔍 Application Number: **JP1998000034257**

🔍 IPC Code: **G09F 3/02; B41M 5/00; B41M 5/40; C09J 7/02;**

🔍 Priority Number: **1998-01-30 JP1998000034257**  
**1998-01-30 JP1998199834257**

🔍 Abstract:

PROBLEM TO BE SOLVED: To provide a very thin image forming body free from unfamiliar feeling in the senses of touch and sight when bonded, having a feeling integrated with an optional object, free from deterioration of an image and generation of a disfigured image, capable of selecting freely an image such as a pattern, a character, or a figure when used, and capable of bonding it to the optional object.


SOLUTION: This body is composed of a image receptor where a mold releasing agent 2 and an image receiving layer 3 are formed in order on one face of a sheetlike base material 1, and a sticking body where an adhesive layer 5, an urethane resin layer 6, an adhesive layer 7, and a mold releasing sheet 8 are formed in order on one face of a separator 4. Adherence strength of the base material 1 is 40-80 g, adherence strength of the separator 4 is 25-39 g, and adherence strength of the sheet 8 is 8-24 g respectively in T-type adhesion test at 180 degree.

COPYRIGHT: (C)1999,JPO

🔍 INPADOC Legal Status: None **Get Now:** [Family Legal Status Report](#)

🔍 Family: [Show 2 known family members](#)

🔍 Other: DERABS C1999-503734 DERABS C1999-503734



[View Image](#)

1 page